

: THE PUBLIC BIDDING OF:
 IF SUBMISSION OF BIDS:

UPLB-I-046-12-17 SUPPLY AND DELIVERY OF CONSTRUCTION MATERIALS AND ELECTRICAL SUPPLIES FOR UHO
Monday, December 11, 2017 1:15PM

LOT #	ITEM #	REQUIRED SECIFICATIONS	OFFERED SPECIFICATIONS (write down detailed offered specifications)	REFERENCES (include supporting documents)	COMMENTS/ REMARKS (clarify inclusion/ exclusion)	EVALUATION
		CONSTRUCTION MATERIALS FOR STAFF HOUSING FC: 8217400 RCC: LB03015001-C0000683 End-user: Mr. James Suizo				
1	1	Marine Plywood, 1/4"x4"x8", 5mm x 1.22m x 2.44m				
	2	Galvanized Iron Plain Sheet, Gauge #24 0.5mm thk x 4' x 8'				
	3	Corrugated Sheet, Pre-painted, Baguio Green, 4' x 8' x 12' GA #24				
	4	LED Bulb, 10 watts, E27 cap, white, 220-240V 1500 lifetime hours, energy efficient label at, 1055 minimum output lumens, BPS certified, ISO certified				
	5	Semi gloss Latex Paint, UPLB beige color, Premium quality				
	6	Wood Liston 1/2' x 2' x 12', S4S KD				
		CONSTRUCTION MATERIALS AND ELECTRICAL SUPPLIES FOR REWIRING AND INSTALLATION OF ELECTRIC KILOWATT HOUR AT THE ATI-NTC DORM FC: 8219700 RCC: LB03015001-C0000689 End-user: Mr. James Suizo				
2	1	PVC pipe 63mm Ø x 3 m, Thick wall, powerline, 80 joules Izod Impact, 55Mpa Tensile Strength, 90% k65 Grade resin by Mass PNS 14, neltex"brand or approved equal				
	2	PVC pipe 50mm Ø x 3 m, Thick wall, powerline, 80 joules Izod Impact, 55Mpa Tensile Strength, 90% k65 Grade resin by Mass PNS 14, neltex"brand or approved equal				
	3	PVC pipe 25mm Ø x 3 m, Thick wall, powerline, 80 joules Izod Impact, 55Mpa Tensile Strength, 90% k65 Grade resin by Mass PNS 14, neltex"brand or approved equal				
	4	PVC pipe 20mm Ø x 3 m, Thick wall, powerline, 80 joules Izod Impact, 55Mpa Tensile Strength, 90% k65 Grade resin by Mass PNS 14, neltex"brand or approved equal				
	5	PVC pipe 25mm Ø 90 m, Thick wall, powerline, 80 joules Izod Impact, 55Mpa Tensile Strength, 90% k65 Grade resin by Mass PNS 14, neltex"brand or approved equal				
	6	PVC pipe 20mm Ø 90 m, Bend, Long Sweep, Thick wall, 80 joules Izod Impact, 55Mpa Tensile Strength, 90% k65 Grade resin by Mass PNS 14, neltex"brand or approved equal				
	7	PVC Adapter, 63mm, Ø 80 Joules Izod Impact, 55Mpa Tensile Strength, 90% k65 Grade resin by Mass PNS 14, neltex"brand or approved equal				

: THE PUBLIC BIDDING OF:
 IF SUBMISSION OF BIDS:

UPLB-I-046-12-17 SUPPLY AND DELIVERY OF CONSTRUCTION MATERIALS AND ELECTRICAL SUPPLIES FOR UHO
Monday, December 11, 2017 1:15PM

LOT #	ITEM #	REQUIRED SECIFICATIONS	OFFERED SPECIFICATIONS (write down detailed offered specifications)	REFERENCES (include supporting documents)	COMMENTS/ REMARKS (clarify inclusion/ exclusion)	EVALUATION
	8	PVC Adapter, 50mm, Ø 80 Joules Izod Impact, 55Mpa Tensile Strength, 90% k65 Grade resin by Mass PNS 14, neltex"brand or approved equal				
	9	PVC Adapter, 25mm, Ø 80 Joules Izod Impact, 55Mpa Tensile Strength, 90% k65 Grade resin by Mass PNS 14, neltex"brand or approved equal				
	10	PVC Adapter, 20mm, Ø 80 Joules Izod Impact, 55Mpa Tensile Strength, 90% k65 Grade resin by Mass PNS 14, neltex"brand or approved equal				
	11	Steel Locknut & Bushing 63mmØ				
	12	Steel Locknut & Bushing 50mmØ				
	13	Steel Locknut & Bushing 25mmØ				
	14	Steel Locknut & Bushing 20mmØ				
	15	Flexible Metalic Conduit (FMC), 20 mmØ				
	16	FMC Metal Connector, 20mmØ				
	17	G.I. Utility Box, 2 x 4", Ga #16,Deep Type				
	18	G.I. Junction Box with cover, 4" x 4, Ga #16,Deep Type				
	19	G.I. Square Box with cover, 4 x 4, Ga #16,Deep Type				
	20	Vynil Electrical Tape, 7 mils thick, 3/4" x 36/rl, 3M"brand or approved equal				
	21	Rubber tape, self-fusing, 30mils thickm 3/4" x 22'rl, 3M brand or approved equal				
	22	PVC pipe Solvent Cement, 'Neltex Brand or approved equal 400cc/can				
	23	Red Oxide printer paint				
	24	G.I Tire wire, Ga no.16 (52mtr/kg)				
	25	Unplasticized PVC Moulding 3/4" x 8				
	26	5.5mm ² Stranded THW, 5.27mm Ø 70.90 kg/km, 35A @ 75'c UL83 ASTM;b3, B8, ICEA S 16-402, UL Approved, PNS 35 Phelps Dodge" brand or approved equal				
	27	3.5mm ² Stranded THW, 4.67mm Ø 49,kg/km, 25A @ 75'c UL83				
	28	2.0mm ² Stranded THW, 4.2mm Ø 35.50,kg/km, 20A @ 75'c UL83 ASTM;b3, B8, ICEA S 16-402, UL Approved, PNS 35 Phelps Dodge" brand or approved equal				
	29	Three Gang Switch with face plate and cover, 16A, 250 V, Wall mounted Recessed type, Non-screw connecting Hole (Global IEC Base Technology) conform to IEC60669-I Stranded BPS Certified Product Safety License No. Q-1168/1169."Panasonic"Brand				

: THE PUBLIC BIDDING OF:
 IF SUBMISSION OF BIDS:

UPLB-I-046-12-17 SUPPLY AND DELIVERY OF CONSTRUCTION MATERIALS AND ELECTRICAL SUPPLIES FOR UHO
Monday, December 11, 2017 1:15PM

LOT #	ITEM #	REQUIRED SECIFICATIONS	OFFERED SPECIFICATIONS (write down detailed offered specifications)	REFERENCES (include supporting documents)	COMMENTS/ REMARKS (clarify inclusion/ exclusion)	EVALUATION
	30	Duplex Convenience Outlet with safety Shutter face plate				
	31	Tandem outlet, Grounding type with face plate and cover 20A-250V, wall-mounted				
	32	1 x 5 watts bulb, cool white, 220-240v, Philips brand in 4 Ø porcelain ceiling receptacle				
	33	1 x 3 watts bulb, cool white, 220-240v, Philips brand in 4 Ø porcelain ceiling receptacle				
	34	PPI to PP9-panel board Housing; from Ga #16				
	35	MDP-2 Circuit breakers Branches: 1-15AT, 50AF, 2-pole, 230V				
	36	Wire Gutter, 200mm x 200mm x 900mm, Ga.No.16, pre-molded, pre-painted, powder coated finish				
	37	Kilowatt Hour Meter in standard meter base, 1-phase, 3 wires 240V, 60HZ, model no.1-210				

Note: Please fill-up applicable columns.

Signature of Representative: _____

Name of Representative: _____

Position: _____

Company: _____

Address: _____

Telephone/ Fax: _____

Email: _____

End-user:

 Signature over Printed Name