


UNIVERSITY OF THE PHILIPPINES

LOS BANOS Los Banos, IV-A

VAT Reg. TIN: 000-864-006-00004

Request for Quotation/ Bid Form (Technical Specifications) BAC UPLB



Balenson 8 180 4

Janet Da48

				UPLB-RQ-
	7			DEADLINE OF SUBMISSION:
ppliers Name:		Date	April 12, 2021	
		Fund Code: MOP: Contact No:	Public bidding	

Contact Person

Please quote your lowest price on the item/s listed below, subject to the General Conditions below.

- 1. Bidders shall provide correct and accurate information required in this form. All entries must be typewritten or in print and properly accomplished. Do not leave blank entries, put N/A for not applicable.
- 2. Price quotation/s to be denominated in Philippine Peso shall include all taxes, duties, and/ or levies payable.

 3. Bidders must indicate the BRAND and MODEL NUMBER for equipment and its accessories or peripherals. Evidence shall be in the form of manufacturer's un-amended sale literature, unconditional statement of specification and compliance issued by the manufacturer and sample.

 4. Quotation through fax/email is acceptable. Winning bidder shall submit original signed RQ before issuance of Puchase order (P.O.).

 5. Quotations exceeding the Approved Budget for Contract shall be rejected.

 6. Documentary requirements per Memorandum No. 03 Series of 2017 shall be attached upon submission of the quotation

 7. Others: ______

ITEM No.	GENERAL NAME OF THE ITEM	REQUIRED SPECIFICATIONS	UNIT OF MEASURE	QTY	ESTIMATED UNIT APPROVED BUDGET OF THE CONTRACT	ESTIMATED TOTAL APPROVED BUDGET OF THE CONTRACT	OFFERED SPECIFICATION Suppliers must state here the detailed technical specifications of their offer against each of the individual parameters of each requirements	QUOTED UNIT PRICE	TOTAL QUOTED PRICE	EVALUATION (Leave this space blank, For BAC/ Evaluators only
1	lot	Supply and Delivery, Branded and brand newm, Surveillance system of BACSec-UPLB								
1	Recorder (NVR)	Branded and brand new, Video And Audio; IP Video Input: 8-ch HDMI Output: 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz VGA Output: HDMI,VGA CVBS Output: 1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480 Incoming Bandwidth: 80 Mbps 256 Mbps Audio Output: 1-ch, RCA (Linear, 1 KΩ) Two-Way Audio: 1-ch, RCA (2.0 Vp-p, 1 k Ω) Decoding; Decoding Format: H.265+,H.265,H.264+,H.264 Decoding Capability: 16-ch@1080p Synchronous Playback: 8-ch Recording Resolution: 12 MP/8 MP/6 MP/5 MP/4 MP/3MP/1080p/UXGA/720p /VGA/4CIF //DCIF/2CIF/QCIF Network Network Protocol: TCP/IP, DHCP, Hik-Connect, DNS, DNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS Remote Connection: 32 Network Interface: 1 RJ-45 10/100/1000 Mbps self- adaptive Ethernet interface PoE;	set	1	P 10,800.00	P 10,800.00				
		Interface: 8 RJ-45 10/100 Mbps self-adaptive Ethernet interfaces Power: \$ 120 W ≤ 180 W Standard: IEEE 802.3 af/at Auxiliary Interface; SATA: 2 SATA interfaces Capacity: Up to 8TB capacity for each HDD USB Interface: Front panel: 1 × USB 2.0; Rear panel: 1 × USB 3.0 Alarm In/Out: 4/1 General; Power Supply: 100 to 240 VAC, 50 to 60 Hz Consumption: ≤15 W (without enabling PoE) Dimension (W × D × H): 385 × 315× 52 mm (15.2" × 12.4" × 2.0") ≤ 3 kg (6.6 lb) Rackmountable, 1U Product manual, metal ear mount kits, USB mouse, Sata data and power cables and PSU included; Warranty: 1 year on parts, repair and services.								

2	Bullet Camera	Branded and brand new,	рс	2	P	2,500.00	P	5,000.00		
		Camera; Image Sensor: 1/2.8" Progressive Scan CMOS Min. Illumination: Color: 0.028 Lux @ (F2.0, AGC ON), 0						,		
		Lux with IR								
		Shutter Speed: 1/3 s to 1/100,000 s Slow Shutter: Yes								
		Day &Night: IR cut filter								
		Wide Dynamic Range: Digital WDR								
		Lens; Lens: Fixed lens, 2.8/4 mm								
		Aperture: F2.0						l,		
		FOV: 2.8mm: Horizontal FOV: 114°, vertical FOV: 62°,								
		diagonal FOV: 135° Lens Mount: M12								
		Illuminator;								
		IR Range: Up to 30 meters								
		Wavelength: 850 nm Video;								
		Max. Resolution: 1920 × 1080			_					
		Video Compression: Main stream:								
		H.265+/H.265/H.264+/H.264;Sub-stream: H.265/H.264/MJPEG								
		H.264 Type: Baseline Profile/Main Profile/High Profile								
		H.265 Type: Main Profile								
		Video Bit Rate: 32 Kbps to 8 Mbps Smart Feature-Set;								
		Region Of Interest: 1 fixed region for main stream and sub-								
		stream								
		Image;								
		Image Enhancement: BLC, 3D DNR Image Setting: Rotate mode, saturation, brightness,								
		contrast, sharpness, AGC and white balance adjustable by								
		client software or web browser								
		Day/Night Switch: Day/Night/Auto/Schedule Main Stream Max. Frame Rate: 50Hz: 25fps (1920 × 1080,								
		1280 × 960, 1280 × 720);60Hz: 30fps (1920 × 1080, 1280 ×								
		960, 1280 × 720)			_					
		Sub-Stream Max. Frame Rate: 50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720),60Hz: 30fps (1920 × 1080, 1280 ×								
		960, 1280 × 720)								
		Network								
		Protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X,								
		QoS, IPv6, UDP, Bonjour								
		API: ONVIF (PROFILE S, PROFILE G), ISAPI								
		Simultaneous Live View: Up to 6 channels User/Host: Up to 32 users,3 levels: Administrator,								
		Operator, and User								
		Client: iVMS-4200, Hik-Connect, iVMS-5200								
		Alarm Trigger: Motion detection, video tampering alarm, illegal login								
		Web Browser: IE8+, Chrome 41.0-44, Firefox 30.0-51,								
		Safari 8.0-11								
		Interface Communication Interface: 1 RJ45 self-adaptive Ethernet								
		port								
		General;								
		Firmware Version: 5.5.83 General Function: One-key reset, heartbeat, mirror,								
		password protection, privacy mask, watermark, IP								
		address filter Startup And Operating Conditions: -30 °C to 60 °C (-22 °F								
		to 140 °F), humidity 95% or less (non-condensing)								
		Power Supply: 12 VDC ± 25%, Φ 5.5 mm coaxial power								
		plug; PoE (802.3af, class 3)								
		Material: Front cover: metal, back cover: plastic Dimensions: Camera: 67.8 × 66.2 × 177.6 mm (2.7" × 2.6"								
		× 7")								
		Product manual, mounting kits and drill pattern sticker.								
		Warranty: 1 year on repair, parts and services.								

1 2	Turnet Commen	December 1			-		-		1	
3	Turret Camera	Branded and brand new, Camera	un	6	P	2,500.00	P	15,000.00		
		Image Sensor: 1/2.8" Progressive Scan CMOS Min. Illumination: Color: 0.028 Lux @ (F2.0, AGC ON), 0								
		Lux with IR								
		Shutter Speed: 1/3 s to 1/100,000 s								
		Slow Shutter: Yes								
		Day &Night: IR cut filter								
1		Wide Dynamic Range: Digital WDR								
		Lens								
		Lens: Fixed lens, 2.8/4 mm								
		Aperture: F2.0								
		FOV: 2.8mm: Horizontal FOV: 114°, vertical FOV: 62°,								
		diagonal FOV: 135°								
		Lens Mount: M12								
		Illuminator								
		IR Range: Up to 30 m								
		Wavelength: 850 nm								
		Video								
		Max. Resolution: 1920 × 1080								
		Video Compression: Main stream:								
		H.265+/H.265/H.264+/H.264;Sub-stream:								
		H.265/H.264/MJPEG								
		H.264 Type: Baseline Profile/Main Profile/High Profile H.265 Type: Main Profile								
		Video Bit Rate: 32 Kbps to 8 Mbps								
		Smart Feature-Set								
	1	Region Of Interest: 1 fixed region for main stream and sub-								
	1	stream								
		Image								
		Image Enhancement: BLC, 3D DNR								
		Image Setting: Rotate mode, saturation, brightness,								
		contrast, sharpness, AGC and white balance adjustable by								
1		client software or web browser								
		Day/Night Switch: Day/Night/Auto/Schedule								
		Main Stream Max. Frame Rate: 50Hz: 25fps (1920 × 1080,								
		1280 × 960, 1280 × 720);60Hz: 30fps (1920 × 1080, 1280 ×								
		960, 1280 × 720)								
		Sub-Stream Max. Frame Rate: 50Hz: 25fps (640 × 480,			_					
		640 × 360, 320 × 240);60Hz: 30fps (640 × 480, 640 × 360,								
	1	320 × 240)								
	1 1	Network								
		Protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS,								
	1	DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X,								
		QoS, IPv6, UDP, Bonjour API: ONVIF (PROFILE S, PROFILE G), ISAPI								
	1	Simultaneous Live View: Up to 6 channels								
		User/Host: Up to 32 users,3 levels: Administrator,								
	1 1	Operator, and User								
		Client: iVMS-4200, Hik-Connect, iVMS-5200								
		Web Browser: IE8+, Chrome 41.0-44, Firefox 30.0-51,								
		Safari 8.0-11								
1		Alarm Trigger: Motion detection, video tampering alarm,								
		illegal login								
1		Interface								
1		Communication Interface: 1 RJ45 10M/100M self-								
	1	adaptive Ethernet port								
		General .								
		Firmware Version: 5.5.83								
		General Function: One-key reset, heartbeat, mirror, password protection, privacy mask, watermark, IP								
		address filter								
		Startup And Operating Conditions: -30 °C to 60 °C (-22 °F								
		to 140 °F), humidity 95% or less (non-condensing)								
		Power Supply: 12 VDC ± 25%, Φ 5.5 mm coaxial power								
		plug; PoE (802.3af, class 0)								
		Material: Camera body: metal, bottom base : plastic								
		Dimensions: Camera: 94.4 × Φ110 mm (3.7" × Φ4.3")								
		;With package: 150 × 150 × 141 mm (5.9" × 5.9" × 5.6")								
	1	Camera: Approx. 354 g (0.8 lb.) ;With package: Approx.								
		681 g (1.5 lb.)								
1		Power Consumption And Current: 12 VDC, 0.4 A, max. 5								
	1	W; PoE (802.3af, 36 V to 57 V), 0.20 A to 0.10 A, max. 6.5								
		W								
		Interface Protection: Ingress protection: IP66 (IEC 60529-								
		2013) Product manual, mounting kits and drill pattern sticker								
		Warranty: 1 year on repair, parts and services.			_					

-										
4	Surveillance Drive	Branded and brand new, Capacity: 2 TB Interface: SATA Form Factor: 3.5 Inch Disk Speed (RPM): 5400rpm Type: Purple storage drive Dimensions (L x W x H): 147mm x 101.6mm x 26.1mm Sealed upon delivery and inspection, (not installed in NVR) Warranty: 1 year on repair, parts and services.	рс	1	P	4,000.00		4,000.00		
5	UTP Cable	Branded and brand new, Original Data: Category Se (CATSe) AWG:24 Stranding: Solid Material: BC- Bare Copper Number of Pairs: 4 INSULATION Material: PO - Polyolefin OUTER JACKET MATERIAL: PVC - Polyvinyl Chloride Nom. Diameter: 0.206 in With Ripcord Frequency [MHz]: 100 MHz UL Voltage Rating: 300 V (CMR) Environmental Suitability: Riser, Indoor IEEE: IEEE 802.3bt Type 1, Type 2, Type 3 RoHS 2 compliance 305 meters/1000ft per box	box	1	P	6,000.00		6,000.00		
6	Connector	Branded and brand new, Category: CATS Original RJ45, Stranded Modular Connectors 50 micron Gold plating RoH5 2 compliance Transparent With Rubber Boots	set	20		10.00		200.00		
7	LED Monitor	Branded and brand new, Screen Size: 32" Backlit LED, Full HD 1920 × 1080 Resolution Wide Viewing Angle: 178" H/178" V 3D Comb Filter, 3D De-Interlace, 3D Noise Reduction, Skin Tone Correction HDMI, VGA, BNC, and USB Inputs Audio Input; Built-In Speakers Image Freeze High Reliability, Designed for 24 x 7 Use Metal Bezel for High Durability VESA Mount (200 mm x 200 mm) Manual, Remote with battery and universal wall mount included; Warranty: 1 year on repair, parts and services. Constructional materials	set	1	P	9,000.00		9,000.00		
8	Pullbox	Brand new, PVC, 8" x 8" with cover	pc	1	1	5,000.00	-	5,000.00		
					-					
9	Ubox	Brand new, utility/junction box, PVC, with cover	pc	9						
10		Brand new, PVC Plastic, 3/4" x 8', White,	рс	10						
11	Adhesive	Brand new, synthetic rubber based adhesive, 100gm sachet	рс	5						
12	Pipe	Brand new, PVC, 1/2" x 10', Orange.	pcs	23						
					1	TOTAL ABC	P	60,000.00		

Reviewed and Checked By:

1	SON	
MARK EFRA	MMM, GIRONELLA	
R	AC TWG	

Please quote at your government price (including VAT) and state that the time within which you can make delivery. It will be appreciated if we can have your quotation in the office as soon as possible on or before the deadline stated herein.

JAYBEE M, PUNZALAN BUYER/ END-USER

TOTAL QUOTED AMOUNT IN WORDS:

TERMS AND CONDITIONS:

- 1. Price quotation/s shall be valid for a period of at least (30) calendar days from the date of submission.

 2. In order to assure that manufacturing defects shall be corrected by supplier, a warranty security shall be required from the contract awardee for a minimum period of three (3) months, in the case of EXPENDABLE SUPPLIES, or a minimum of one (1) year warranty and two (2) to three (3) years extended warranty (if applicable) in the case of NON-EXPENDABLE SUPPLIES after acceptance by End-user of the delivered supplies.
- Delivery period within ______ calendar days.
 Award of contract shall be made to the lowest quotation wich complies with the technical specifications, and other terms and condition stated herein
 UPLB reserves the right to reject any or all offers as may be considered most advantageous to the University.
 Any interlineations, erasure, or overwriting shall be valid only if they are signed or initiated by you or any of your duly authorized representative/s.

Requirements for Suppliers (GPPB Resolution No. 21-2017)
REQUIREMENTS Negotiated Procurement-Small Value Procurement Negotiated Procurement-Lease of Real Property or Venue (Section 53.10)

Negotiated Procurement- Scientific, Scholarly or Artistic Work, Exclusive Technology and Media Services (Section 53.6) Negotiated Procurement-Emergency (Section 53.2) Shopping (Section 52) (Section 53.9) 1 Mayor's/Business Permit 2 PhilGEPS Registration Number Revised 6 June 2016/ JOINT BAC RESOLUTION NO. R-006-18

5 1	Income / Business	tax returns (except for government agencies as lessor)		FOR ABC'S ABOVE 500K	/	FOR ABC'S ABOVE 50K
6	Omnibus Sworn Sta	tement		FOR ABC'S ABOVE 50K		FOR ABC'S ABOVE 500K
7	7 NFCC for Infrastructure with ABC above Ph500k			/		FOR ABC'S ABOVE 50K
	aving carefully in of the Company:	read and accepted your General Conditions, I/We quote you	ou on the Item at	prices noted abo	ove.	
Address	s:				Tel. No. :	
				_	Fax No. :	
Signatu Name o	ure over Printed of			_	Email Address:	
Position	n:				Date:	