

## UNIVERSITY OF THE PHILIPPINES LOS BANOS

Los Banos, IV-A VAT Reg. TIN: 000-864-006-00004

## Request for Quotation/ Bid Form (Technical Specifications) <u>Department of Civil Engineering, CEAT</u>

AUG 2 2 2022 -TIL

UPLB-RQ- 8-191-22-GOOPS
DEADLNE OF SUBMISSION

UPLB-RQ-

		DEADLINE OF
Suppliers Name:	Date	January 14, 2022
	Fund Code:	8265200
	MOP:	SAL
	Contact No:	0998-537-3870 (nvaguilar@up.edu.ph)
	Contact Person	Niña Gracia V. Aguilar

## Please quote your lowest price on the item/s listed below, subject to the General Conditions below.

## Note:

- 1. Bidders shall provide correct and accurate information required in this form. All entries must be typewritten or in print and properly accomplished. Do not leave blank entries, put
- 2. Price quotation/s to be denominated in Philippine Peso shall include all taxes, duties, and/ or levies payable.
- 3. Bidders must indicate the BRAND and MODEL NUMBER for equipment and its accessories or peripherals. Evidence shall be in the form of manufacturer's un-amended sale
- 4. Quotation through fax/email is acceptable. Winning bidder shall submit original signed RQ before issuance of Puchase order (P.O.).
- 5. Quotations exceeding the Appoved Budget for Contract shall be rejected.
- 6. Documentary requirements per Memorandum No. 03 Series of 2017 shall be attached upon submission of the quotation
- 7. Others:

ITEM No.	GENERAL NAME OF THE ITEM	REQUIRED SPECIFICATIONS	UNIT OF MEASU RE	I was made	ESTIMATED UNIT APPROVED BUDGET OF THE CONTRACT	ESTIMATED TOTAL APPROVED BUDGET OF THE CONTRACT	OFFERED SPECIFICATION Suppliers must state here the detailed technical specifications of their offer against each of the individual parameters of each requirements	QUOTED UNIT PRICE	TOTAL QUOTED PRICE	EVALUATION (Leave this space blank. For BAC/ Evaluators only)
1		Branded and Brand New Portable Speaker	set	2	39,500.00	79,000.00				

	Technical Specifications					
1 1	Transducer: 2 x 6.5in					
	(176mm) woofers + 2 x 2.5in		1			
	(65mm) tweeters					
	Output power: 240W RMS					
	Frequency response: 45Hz -					
	20kHz (-6 dB) Signal-to-noise				1	
	ratio: >80dBA					
	Power Supply: 100 - 240V -					
	50/60Hz					
						1
	Standby power consumption:					
	< 2 W with BT connecting; <					
	0.5 W without BT connecting					
	Bluetooth® version: 5.1					
	Bluetooth® profile: A2DP 1.3,					
	AVRCP 1.6 Bluetooth®					
	transmitter frequency range:					
	2.4 – 2.48GHz	1 1				
	Bluetooth® transmitter power:					
	15dBm (EIRP) Bluetooth®					
	transmitter modulation: GFSK,					
	π/4 DQPSK, 8DPSK					
	Bluetooth® range: Approx.					
	10m (33ft) USB format:	1 1				
1 1	FAT16, FAT32					
1 1						
	USB file format: mp3, wma,					
	wav Battery type: Lithium-ion					
	72Wh USB output: 5V/2.1A					
	Digital input: Bluetooth / USB-					
	9dBFS Battery charge time:					
	<3.5 hrs Battery playtime: < 18					
	hrs*					
	Product Dimension (W x H x					
	D): 325.6 x 687.7 x 367.8mm /					
	12.8 x 27 x 14.5in					
	Packaging Dimension (W x H					
	x D): 792 x 430 x 388mm /					
	31.18 x 16.93 x 15.28in					
	Net weight: 17.42kg / 38.4 lbs					
	Gross weight: 19.1kg / 42.11					
	lbs					
		THE PERSON NAMED IN				

						***************************************		
2 Audio and	Branded and Brand New	set	2	25,000.00	50,000.00	***************************************		
Visual Equipment	Projector							
Equipment	Projectors Facets: Resolution, Projectors Facets: SVGA Contrast Ratio, Projectors Facets: 15,000:1 Brightness Range Lumens, Projectors Facets: 2000 Features, Projectors Facets: Wifi Quick Corner Laser / Lamp, Projectors Facets: Lamp							
	Projection Technology: RGB liquid crystal shutter projection system							
	Brightness2: White Light Output (Normal/Eco): 3,300lm / 2,050lm Colour Light Output: 3,300lm							

Connectivity: USB Interface: USB Type A: 1 (for USB Memory, USB Document Camera, for Wireless LAN Unit, Firmware Update) USB Type B: 1 (for USB Display, Mouse, K/B, Control, Firmware Update) Analog Input: D-Sub 15pin: 1 (Blue molding) Composite: RCA x 1 (Yellow) Digital Input: HDMI: 1 (MHL not supported) Audio Input: 2 RCA (White / Red): 1			
Screen Size (Projected Distance): Standard Size: 60" screen 1.77 - 2.4 m Zoom: Wide: 30" - 350" [0.88 - 10.44 m] Zoom: Tele: 23" - 260" [0.88 - 10.44 m]			

Geometric Correction:  Vertical/Horizontal Keystone: ±30° / ±30° Auto Keystone: Yes (Vertical only) Horizontal Slide Keystone Correction: Yes Quick Corner: Yes Operating Temperature: 5 - 35 °C <41 - 95 °F> (0m / 0ft - 2,286m / 7,500ft) 5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% - 80% humidity, No condensation) Operating Altitude: 0 - 3,000 m <0 - 9,843 ft> (over 1,500m / 4,921ft: with high altitude mode)			
Start-Up Period: About 6 seconds, Warm-up Period: 30 seconds Cool Down Period: Instant Off Internal Speaker(s): Sound Output: 2W Mono			

Air Filter: Maintenance Cycle*4: 6,000 hours / 10,000 hours Fan Noise: Fan Noise (Normal / Eco): 37dB / 28dB Power: Power Supply Voltage: 100 - 240 V AC ±10%, 50/6				
Network: Wireless: Yes (Optional) Start Up Period: About 6 seconds, Warm-up Period: 30 secon Optional Wireless & Built Lan Specifications: Supported Speed For Each Mode*3: IEEE 802.11b (2.4GHz): 11 Mbps IEEE 802.11g (2.4GHz): 54 Mbps	In			
IEEE 802.11n (2.4GHz): 13 Mbps Wireless LAN Security: Quick Mode: WPA2-PSK, Advanced Mode: WPA/WP PSK Supported Connection Mode: Infrastructure, Access Poin	A2-			

	Specifications of Main Parts: LCD: Size: 0.55" (D7) Native Resolution: SVGA Lamp: Type: 210W UHE Life (Normal / Eco)*1: 6,000 hours / 10,000 hours						
Audio and Visual Equipment	Branded and Brand New Camcorder and Accessories	set	1	97,450.00	97,450.00		
	SENSOR TYPE  1/2.5 type (0.28 in [7.20 mm]) back-illuminated Exmor R  CMOS Sensor  EFFECTIVE PIXELS (VIDEO) approx. 8.29 Megapixels (16:9)2  EFFECTIVE PIXELS (STILL IMAGE) approx. 8.29 Megapixels (16:9) / approx. 6.22 Megapixels (4:3)						
	IMAGE PROCESSOR BIONZ X image processor						

LENS TYPE  Zeiss® Vario-Sonnar® T*  FILTER DIAMETER  55 mm  LENS COVER  Auto  APERTURE  F 2.0-3.8  FOCAL DISTANCE  f = 4.4 to 88 mm  FOCAL LENGTH (35 MM  EQUIVALENT) (VIDEO)  f = 1-1/16 to 21-1/8 inch 2, f=26.8-536.0 mm (16:9)  FOCAL LENGTH (35 MM  EQUIVALENT) (STILL  IMAGE)  f = 1-1/16 to 21-1/8 inch (16:9), f = 1-5/16 to 25-7/8 inch (4:3), f = 26.8 to 536.0  mm (16:9), f = 32.8 to 656.0  mm (4:3)  MINIMUM FOCUS  DISTANCE  approx. 1 cm (Wide), approx. 80 cm (Tele) (approx. 13/32 inch (Wide), approx. 31-1/2 inch (Tele))  IRIS DIAPHRAGM 6 blades		
OPTICAL ZOOM 20x CLEAR IMAGE ZOOM 4K: 30x, HD: 40x3 DIGITAL ZOOM 250x4		

7.5 LC Wii TO Ye: BR Ye: MA Gri	REEN TYPE cm (3.0 type) Clear Photo D display (460,800 dots) de (16:9) UCH PANEL s IIGHTNESS CONTROL s (Menu)5 IRKER/GRID DISPLAY d Line6 IGLE ADJUSTMENT ening angle: max. 90 deg.; ming angle: max. 270 deg.			
TY Ba w/	AGE STABILIZATION PE lanced Optical SteadyShot Intelligent Active mode (5- is)7			
FA FA Ye LO	OCUS TYPE Intrast AF OCUS MODE Ito / Manual (Touch Panel) OCUS AREA Ill range focus / spot focus AST INTELLIGENT AF IS OCK-ON AF ICK-ON			

MODE Auto, Flexible Spot (Touch Panel), Manual (Menu) METERING MODES Multi-segment / Spot EXPOSURE COMPENSATION AE Shift (Touch Panel) LOW LUX MODE Yes AUTO IRIS CONTROL F2.0-F11 MANUAL IRIS CONTROL F2.0-F11 MANUAL EXPOSURE ASSIST Zebra Pattern Display BACKLIGHT COMPENSATION Yes (Auto) GAIN CONTROL Auto AGC LIMIT			
MINIMUM ILLUMINATION 4K: Standard: 9 lux (1/60 shutter speed), HD: Standard: 6 lux (1/60 shutter speed), 4K: Low Lux 1.8 lux (1/30 shutter speed), HD: Low Lux 1.2 lux (1/30 shutter speed)			

MEDIA TYPE  XAVC S 4K (100 Mbps): SDHC Memory Card (4 GB or over, UHS-I U3 or higher) / SDXC Memory Card (UHS-I U3 or higher), XAVC S 4K (60 Mbps): SDHC Memory Card (4 GB or over, Class 10 or higher) / SDXC Memory Card (Class 10 or higher), XAVC S HD: SDHC Memory Card (4 GB or over, Class 10 or higher) / SDXC Memory Card (Class 10 or higher), AVCHD, Still: Memory Stick PRO-HG Duo, Memory Stick PRO-HG Duo, Memory Stick XC-HG Duo, SD/SDHC / SDXC			
HG Duo, SD / SDHC / SDXC Memory Card (Class 4 or higher)			

	RECORDING FORMAT			
	(VIDEO)			
	XAVC S format: MPEG4-AVC			
	/ H.264, AVCHD format ver.			
	2.0 compatible: MPEG4-AVC /			
	H.264, MP4: MPEG-4 AVC /			
	H.264			
	VIDEO RESOLUTION			
	XAVC S 4K: 3840 x 2160 /			
	30p, 24p, XAVC S HD: 1920 x			1 1
	1080 / 60p, 30p, 24p, AVCHD:			
	1920 x 1080 / 60p (PS), 30p			
	(FX, FH), 24p (FX, FH), 60i			
	(FX, FH), 1440 x 1080 / 60i			
1	(HQ, LP), MP4: 1280 x 720 /			
	30p			
	VIDEO RECORDING RATE			
	(ABR / VBR)			
	XAVC S 4K: approx. 100			
	Mbps, XAVC S 4K: approx. 60			
	Mbps, XAVC S HD: approx.			
	50 Mbps, AVCHD PS: approx.			
	28 Mbps / FX: approx. 24			
	Mbps / FH: approx. 17 Mbps /			
	HQ: approx. 9 Mbps / LP:			
	approx. 5 Mbps, MP4: approx.		1	
	3 Mbps10			
	RECORDING FORMAT			
	(STILL IMAGE)			
	JPEG (DCF Ver. 2.0			
	compatible, Exif Ver. 2.3			
	compatible, MPF Baseline			
	compatible)			
1 1				

STILL IMAGE SIZE (PHOMODE) L: 16.6 Megapixels 16:9 (5x 3056), 12.5 Megapixels 4 (4080 x 3056), M: 8.3 Megapixels 16:9, (3840 x 2160), 6.2 Megapixels 4:3 (2880 x 2160), S: 2.1 Megapixels 16:9 (1920 x 1080), 0.3 Megapixels 4:3 (640 x 480) STILL IMAGE SIZE (MOV MODE) M: 8.3 Megapixels 16:9 (3840x2160), S: 2.1 Megapixels 16:9 (1920 x 1080) STILL IMAGE SIZE (PHO CAPTURE) XAVC S 4K: 8.3 Megapixel 16:9 (3840x2160), XAVC S HD: 2.1 Megapixels 16:9 (1920 x 1080) STILL IMAGE SIZE (PHO CAPTURE) XAVC S 4K: 8.3 Megapixel 16:9 (1920x1080), AVCHD: 2.1 Megapixels 16:9 (1920x1080), STILL IMAGE SIZE (TIME LAPSE CAPTURE) 1920 x 1080), 3840 x 2160 HD: S (2.1 M, 4K: L (8.3 M)	E CO S		

STILL IMAGE SIZE (DUAL RECORD) M: 8.3 Megapixels 16:9 (3840 x 2160), S: 2.1 Megapixels 16:9 (1920 x 1080)81112			
BATTERY TYPE InfoLITHIUM with AccuPowerTM Meter System (V Series)22 POWER CONSUMPTION (LCD) 4K: 5.1 W23 POWER CONSUMPTION (VIEWFINDER) -23 POWER REQUIREMENTS 6.8 V/7.3 V (battery pack), 8.4V (AC Adapter) CHARGE ON CAMCORDER (CHARGING TIME WITH SUPPLIED BATTERY) Yes (approx. 3h 25min)24 USB CHARGING DC 5 V 1500 mA			
ACCESSORIES Remote Controlled Tripod			
Memory Card 256gb			
Shoulder Bag			
Studio Light Diffuser			
LED Lights			
 Capture Card			

Compatible with the MI Shoe Digital Audio Interface for low noise and high-quality sound soise and high-quality sound without additional equipment without additional equipment and camera operator capture without additional equipment and camera operator capture without additional equipment and solve the camera capture and solve the capture and s	4	Audio and Visual Equipment	Branded and Brand New Wireless Microphone	unit	2	20,000.00	40,000.00		
mic recording for easy subject and camera operator capture without additional equipment  A wireless microphone ideal for vlogging  Brand and Brand New Shotgun Microphone Equipment  High-performance, monaural microphone picks up targeted (not surrounding) sound. More compact and approx. 15% shorter than the current ECM-CGS0 model. Included microphone holder absorbs zoorning noise from the camera. 3.5 gold coating L type stereo mini plug cable length approx. 35 cm (13 7/8 in). Uses plug-in power or a single AAA alkaline battery.			Digital Audio Interface for low						
for vlogging    Saudio and Visual Equipment   Shotgun Microphone   Unit   1   16,200.00			mic recording for easy subject and camera operator capture						
Visual Equipment  High-performance, monaural microphone picks up targeted (not surrounding) sound. More compact and approx. 15% shorter than the current ECM-CG50 model. Included microphone holder absorbs zooming noise from the camera.  3.5 gold coating L type stereo mini plug cable length approx. 35 cm (13 7/8 in). Uses plug-in power or a single AAA alkaline battery.									
microphone picks up targeted (not surrounding) sound. More compact and approx. 15% shorter than the current ECM-CG50 model. Included microphone holder absorbs zooming noise from the camera. 3.5 gold coating L type stereo mini plug cable length approx. 35 cm (13 7/8 in). Uses plug-in power or a single AAA alkaline battery.	5	Visual		unit	1	16,200.00	16,200.00		
TOTAL ABC 282,650.00			microphone picks up targeted (not surrounding) sound. More compact and approx. 15% shorter than the current ECM-CG50 model. Included microphone holder absorbs zooming noise from the camera. 3.5 gold coating L type stereo mini plug cable length approx. 35 cm (13 7/8 in). Uses plug-in power or a single						
TOTAL QUOTED AMOUNT IN WORDS:			TO	TAL ABC					

MR. ANDREW PALICARDO BACAWG						
e quote at your government price ( ffice as soon as possible on or bef				NIÑA GRAV. GUILAR	eciated if we can ha	ve your quotation in
MS AND CONDITIONS: ce quotation/s shall be valid for a peri- order to assure that manufacturing de	fects shall be corrected by sup	ys from the date oplier, a warranty	of submission. security shall be r	required from the contract award	dee for a minimum pe	riod of three (3) month
livery period within 30 calendar yard of contract shall be made to the lot be reserves the right to reject any or y interlineations, erasure, or overwriting the contract of t	owest quotation wich complies all offers as may be considere ng shall be valid only if they are	d most advanta	geous to the Univ	ersity.		
irements for Suppliers (GPPB Res	Shopping (Section 52)	Negotiated Procurement- Small Value Procurement (Section 53.9)	Negotiated Procurement- Lease of Real Property or Venue (Section 53.10)	Negotiated Procurement- Scientific, Scholarly or Artistic Work, Exclusive Technology and Media Services (Section 53.6)		
REQUIREMENTS	/	/	/	/	/	
Mayor's/Business	/	/	/	/	/	
PhilGEPS		/		/	100 100	
Professional		/				
(for Infrastructure)		FOR ABC'S ABOVE 500K	/	/	FOR ABC'S ABOVE 50K	
Business tax retums (except for government agencies as lessor)		FOR ABC'S ABOVE 50K			FOR ABC'S ABOVE 500K	
7 Omnibus Sworn		1			FOR ABC'S	
NFCC for Infrastructure with ABC above Ph500k			1	I	Linouesau	

Address:	Tel. No. :	
	Fax No.:	
Sign	Email Address:	
Position:	Date:	