

UNIVERSITY OF THE PHILIPPINES LOS BANOS

VAT Reg. TIN: 000-864-006-00004

Request for Quotation/ Bid Form (Technical Specifications) UPLB University Planning & Maintenance Office

BY: Du	DATE: 6/16/202
JUN	2 6 2023
LIDIR-PO- (o	-048-23-I -

DEADLNE OF SUBMISSION

TAR SECRETARIAN

UPLB-RQ-	
DEADLINE OF SUBMISSION	t:
05/17/2023	
8249800	
Shopping	
(049) 536-2447	

Eneleen S. Cerbito

Please duote your lowest price on the item/s listed below, subject to the General Conditions below.

Date Fund Code: MOP:

Contact No.

Contact Person

Note:
1. Bidders shall provide correct and accurate information required in this form. All entries must be typewritten or in print and properly accomplished. Do not leave blank entries, put N/A for not applicable.

- 2. Price quotation/s to be denominated in Philippine Peso shall include all taxes, duties, and/ or levies payable.
 3. Bidders must indicate the BRAND and MODEL NUMBER for equipment and its accessories or peripherals. Evidence shall be in the form of manufacturer's un-amended sale literature, unconditional statement of specification and compliance issued by the manufacturer and sample.
 4. Quiotation through faxional is acceptable. Winning bidder shall submit original signed RO before issuance of Puchase order (P.O.).
 5. Quiotations exceeding the Approved Budget for Contract shall be rejected.
 6. Documentary requirements per Memorandum No. 03 Senes of 2017 shall be attached upon submission of the quotation.
 7. Others:

(TEM #	GENERAL NAME OF THE ITEM	REQUIRED SPECIFICATIONS	UNIT OF MEASURE	QTY	ESTIMATED UNIT APPROVED BUDGET OF THE CONTRACT	ESTIMATED TOTAL APPROVED BUDGET OF THE CONTRACT	OFFERED SPECIFICATION Suppliers must state here the telialist interests applications of prior of or applied mode of the kiddled puremeters of each ringsteamers	QUOTED UNIT PRICE	TOTAL QUOTED PRICE	(Leave ti space bland BAC/ Evaluations)
1		High Bay LED 200W, 6500K, UL Listed 5 years warranty, Luminous Efficacy: 160lm/W Luminous Flux: 40,000lm Input Voltage: 100-305VAC Drvier Efficiency: >92% Power Factor: >0.95 Surge Protection: 4kV(Line-Line): 6kV (Line-Earth) Non-dimmable Beam Angle: 90° Design Life: >>50,000 hours Operating Temperature: -40 ~ +50°C Housing Color: Black Housing Materials: Diecast Aluminum Diffuser Materials: Polycarbonate Ingress Protection: IP65	8	set	12,000.00	96,000.00				
2		High Bay LED 250W, 6500K, UL Listed 5 years warranty, Luminous Efficacy: 160lm/W Luminous Flux: 40,000lm Input Voltage: 100-305VAC Drvier Efficiency: >92% Power Factor: >0.95 Surge Protection: 4kV(Line-Line): 6kV (Line-Earth) Non-dimmable Beam Angle: 90° Design Life: >>50,000 hours Operating Temperature: -40 ~ +50°C Housing Color: Black Housing Materials: Diecast Aluminum Diffuser Materials: Polycarbonate Ingress Protection: IP65	6	set	13,500.00	81,000.00				

C

	3		Flood Light LED 200W 6500K, UL Listed 3 years warranty Luminous Efficacy: 140lm/W Luminous Flux: 28,000lm Input Voltage: 100-305VAC, 50/60Hz Power Supply Efficiency: >90% Power Factor: >0.95 Surge Protection: 4kV(Line-Line): 6kV (Line-Ground) Non-dimmable Beam Angle: 60° Design Life: >>50,000 hours Operating Temperature: -40 -+40°C Housing Materials: Diecast Aluminum Diffuser Materials: Polycarbonate Ingress Protection: IP66	6	set	12,000.00	72,000.00		
	4	Electrical Supplies	Flood Light LED 200W 3000K, UL Listed, 3 years warranty Luminous Efficacy: 140lm/W Luminous Flux: 28,000lm Input Voltage: 100-305VAC, 50/60Hz Power Supply Efficiency: >90% Power Factor: >0.95 Surge Protection: 4kV(Line-Line): 6kV (Line-Ground) Non-dimmable Beam Angle: 60° Design Life: >>50,000 hours Operating Temperature: -40 -+40°C Housing Materials: Diecast Aluminum Diffuser Materials: Polycarbonate Ingress Protection: IP66	2	set	12,000.00	24,000.00		
	5		Circuit Breaker, 20AT, 50AF, 2 pole, Bolt-on type, 240V	2	set	800.00	1,600.00		
	6		Circuit Breaker, 30AT, 50AF, 2 pole, Bolt-on type, 240V	4	set	900.00	3,600.00		III
	7		Panel Board: Housing: Gauge #16, NEMA-3R Powder coated ANSI 61 gray finish, End wall with knockouts, standard door with "Corbin" lock, Copper extruded isolated equipment ground, Mechanical lug type, Copper lugs, Feed thru lugs, UL 67, UL 50, UL 943, NEMA PN-1 Main Breaker: 150AT, 225AF,Three-Phase Industrial Type, 240V class, 22kAIC, International common trip UL 489, UL listed, NEMA AB-1. Branches Circuit Breaker: 2 - 20AT, 50AF, 2-Pole, 240V, Bolt-on Type; 4 - 30AT, 50AF, 2-Pole, 240V, Bolt-on type; 2 - 40AT, 50AF, 2-Pole, 240V, Bolt-on type; 4 - 50AT, 50AF, 2-Pole, 240V, Bolt-on type; 2 - 70AT, 100AF, 2-Pole, 240V, Bolt-on type	1	set	55,000.00	55,000.00		
and the second second second second second	8		Electrical wire 5.5mm² (#10 AWG)THHN / THWN-2, copper, stranded, 40+ amperes at 90°C, 4.1 mmØ, 58 kg/km, ASTM: B3, B8; UL83, PNS35, NEC compliant (150m/box)	1	box	9,000.00	9,000.00		

Page 2 of 3

13	Convenience Outlet with cover Grounding type, 3-gang, surface type, 16A, 250V, Heat resistant, Full color wide series, Screw Type, ISO 9001, ISO 14001, IEC60884-1	20	set	312.00	6.240.00	TOTAL AMOUNT:		
12	Royal Cord AWG#8/2C Stranded, copper wire, PVC Insulated / PVC Jacketed,(UL62, PNS 163, ASTM B3, B173 & B174, 75m/rl	1	roll	19,218.75	19,218.75			
11	Flat cord #12/2 PNS 163, UL62, ASTM B174, 300VAC @ 60°C, Res.5.45@20°C, 29.87kg/km, 150m/d	1	roll	3,510.00	3,510.00			
10	Electrical Tape Highland medium grade tape 1700, rubber resin adhessive material, 1000v/mil dielectric strength, 7 mil thick, 90°C/194°F, ¾ x 36'/roll, RoHS compliant, ASTM D 2301, CSA Certified, UL Listed	30	roll	60.00	1,800.00			
9	Electrical wire 3.5mm² (#12 AWG)THHN/ TWWN-2, copper, stranded, 30+ amperes at 90°C, 3.3 mmØ, 37kg/km., ASTM B3, B8 NEC compliant (150m/box)	1	box	6,000.00	6,000.00			

Reviewed and Checked By:	, 5-	
	JOSELITO C. VILLENA	
	BAC TWG	

Please quote at your government price (including VAT) and state that the time within which you can make delivery. It will be appreciated if we can have your quotation in the office as soon as possible on or before the deadline stated herein.

(late)
LACAP
R END-USER

- 1. Price quotation/s shall be valid for a period of at least (30) calendar days from the date of submission.
- 2. In order to assure that manufacturing defects shall be corrected by supplier, a warranty security shall be required from the contract awardee for a minimum period of three (3)
- Delivery period within \(\frac{\pmathcal{\

Requirements for Suppliers (GPPB Resolution No. 21-2017)

REQUIREMENTS	Shopping (Section 52)	Negotiated Procurement- Small Value Procurement (Section 53.9)	Negotiated Procurement- Lease of Real Property or Venue (Section 53.10)	Negotiated Procurement- Scientific, Scholarly or Artistic Work, Exclusive Technology and Media Services (Section 53.6)	Negotiated Procurement- Emergency (Section 53.2)
1 Mayor's/Business Permit	1	1	/	/	1
2 PhilGEPS Registration Number	1		/	/	/
3 Professional license/ CV (consulting services)	- CS	/		/	
4 PCAB License (for Infrastructure)		/			
5 Income / Business tax returns (except for government agencies as lessor)		FOR ABC'S ABOVE 500K	- 1	/	FOR ABC'S ABOVE 50K
6 Omnibus Sworn Statement		FOR ABC'S ABOVE 50K			FOR ABC'S ABOVE 500K
7 NFCC for Infrastructure with ABC above Ph500k		/			FOR ABC'S ABOVE 50K

			ABOVE 50K
	read and accepted your General Conditions, I/We quote you on the Item a	t prices noted above.	
Name of the Company: Address:		Tel. No. : Fax No. :	
Signature over Printed Position:		Email Address Date:	