



UNIVERSITY OF THE PHILIPPINES

LOS BANOS
Los Banos, IV-A
VAT Reg. TIN 000-864-006-00004

Request for Quotation/ Bid Form (Technical Specifications)
INSTITUTE OF CHEMISTRY

UPLB BAC SECRETARIAT

BY: DATE: 11/8/23

NOV 13 2023 - TIL 10AM

UPLB-RQ- 11-520-23-60005

DEADLINE OF SUBMISSION

UPLB-RQ-

DEADLINE OF SUBMISSION:

Suppliers Name:

Date: October 26, 2023
Fund Code: 9390123
MOP: Small Value Procurement
Contact No: (049) 536-2220
Contact Person: Melvin Magat

Please quote your lowest price on the item/s listed below, subject to the General Conditions below.

- Note: 1. Bidders shall provide correct and accurate information required in this form. All entries must be typewritten or in print and properly accomplished. Do not leave blank entries, put N/A for not applicable.
2. Price quotation/s to be denominated in Philippine Peso shall include all taxes, duties, and/ or levies payable.
3. Bidders must indicate the BRAND and MODEL NUMBER for equipment and its accessories or peripherals. Evidence shall be in the form of manufacturer's un-amended sale literature, unconditional statement of specification and compliance issued by the manufacturer and sample.
4. Quotation through fax/email is acceptable. Winning bidder shall submit original signed RQ before issuance of Purchase order (P.O.).
5. Quotations exceeding the Approved Budget for Contract shall be rejected.
6. Documentary requirements per Memorandum No. 03 Series of 2017 shall be attached upon submission of the quotation.
7. Others.

Table with 10 columns: ITEM No., GENERAL NAME OF THE ITEM, REQUIRED SPECIFICATIONS, UNIT OF MEASURE, QTY, ESTIMATED UNIT APPROVED BUDGET OF THE CONTRACT, ESTIMATED TOTAL APPROVED BUDGET OF THE CONTRACT, OFFERED SPECIFICATION, QUOTED UNIT PRICE, TOTAL QUOTED PRICE, EVALUATION. Row 1: Analog Camera, 2 units, 2,150.00 unit price, 4,300.00 total price.

		GENERAL							
		Material Enclosure: Plastic, Main body: Metal							
		Dimension: Approx. Ø 109.8 mm × 89.75 mm (Ø 4.32" × 3.53")							
		Weight: Approx. 310 g (0.68 lb.)							
		Operating Condition: -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)							
		Communication: Up the coax, Protocol: -C (TVI output)							
		Language: English							
		Power Supply: 12 VDC ±25%							
		Consumption: Max. 4 W							
		IR Range: Up to 20 m							
		APPROVAL							
		Protection: 1P67							
		Compatible with HIKVISION Digital Video Recorder (DVR) Model: DS-7216HQHI-K1							
		Sticker pattern and mounting kits included; Officially sealed upon inspection; Warranty: 1 year on parts and services							
2	IP Camera	Branded and Brand New 2 MP Fixed Dome type Network Camera	un	5	3,630.00	18,150.00			
		CAMERA							
		Image Sensor: 1/2.7" Progressive Scan CMOS							
		Min. Illumination: Color: 0.01 Lux @(F2.0, AGC ON), B/W: 0 Lux with IR							
		Shutter Speed: 1/3 s to 1/100,000 s With Slow Shutter							
		Wide Dynamic Range: Digital WDR							
		Day & Night: IR cut filter							
		Angle Adjustment: Pan: 0° to 355°, tilt: 0° to 75°							
		LENS							
		Focal Length & FOV:							
		2.8 mm, horizontal FOV 112.1°, vertical FOV 60.0°, diagonal FOV 132.2°							
		4 mm, horizontal FOV 90.2°, vertical FOV 48.6°, diagonal FOV 107.6°							
		Lens Mount: M12							
		Focus: Fixed							
		Aperture: F2.0							
		ILLUMINATOR							
		IR Wavelength: 850 nm							
		IR Range: Up to 30 m							
		VIDEO							
		Max. Resolution: 1920 × 1080							
		Main Stream: 50 Hz: 25 fps (1920 × 1080, 1280 × 720) 60 Hz: 30 fps (1920 × 1080, 1280 × 720)							
		Sub-Stream: 50 Hz: 25 fps (640 × 480, 640 × 360) 60 Hz: 30 fps (640 × 480, 640 × 360)							
		Video Compression: Main Stream: H.265/H.264 Sub-Stream: H.265/H.264/MJPEG							
		Video Bit Rate: 32 Kbps to 8 Mbps							
		H.264 Type: Baseline Profile/Main Profile/High Profile							
		H.265 Type: Main Profile							

	H.264+: Main Stream supports								
	H.265+: Main Stream supports								
	Region Of Interest (ROI): 1 fixed region for main stream								
	NETWORK								
	Protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP™, SMTP, IGMP, 802.1X, QoS, IPv6, Bonjour, IPv4, UDP, SSL/TLS								
	Simultaneous Live View: Up to 6 channels								
	API: Open Network Video Interface, ISAPI								
	User/Host: Up to 32 users. 3 levels: administrator, operator and user								
	Web Browser:								
	Plug-in required live view: IE 10+								
	Plug-in free live view: Chrome 57.0+, Firefox 52.0+								
	Local service: Chrome 57.0+, Firefox 52.0+								
	IMAGE								
	Image Settings: Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser.								
	Day/Night Switch: Day, Night, Auto, Schedule								
	Image Enhancement: BLC, 3D DNR								
	INTERFACE								
	Ethernet Interface: 1 RJ45 10 M/100 M self-adaptive Ethernet port								
	EVENT								
	Basic Event: Motion detection, video tampering alarm, exception								
	GENERAL								
	Linkage Method: Upload to FTP, notify surveillance center, send email								
	Camera Material: Metal & Plastic								
	Camera Dimension: Approx. Ø111 mm × 82.4 mm (Ø4.4" × 3.2")								
	Package Dimension: Approx. 134 mm × 134 mm × 108 mm (5.3" × 5.3" × 4.3")								
	Camera Weight: Approx. 410 g (0.9 lb.)								
	With Package Weight: Approx. 610 g (1.3 lb.)								
	Storage Conditions: -30 °C to 60 °C (-22 °F to 140 °F). Humidity: 95% or less (non-condensing)								
	Startup And Operating Conditions-30 °C to 60 °C (-22 °F to 140 °F). Humidity: 95% or less (non-condensing)								
	Web Client Language: English								
	General Function: Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter								
	Firmware Version: V5.5.120								
	Power Consumption And Current:								
	12 VDC, 0.4 A, max. 5 W								
	PoE: (802.3af, 36 V to 57 V), 0.2 A to 0.15 A, max. 6.5 W								
	Power Supply:								
	12 VDC ± 25%								
	PoE: 802.3af, Class 3								
	Power Interface: Ø5.5 mm coaxial power plug								
	APPROVAL								
	EMC: FCC SDoC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 50130-4: 2011 +A1: 2014); RCM (AS/NZS CISPR 32: 2015); IC VoC (ICES-003: Issue 6, 2016); KC (KN 32: 2015, KN 35: 2015)								

		Safety: UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013, IEC 62368-1:2014); CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013, IEC 62368-1:2014); BIS (IS 13252(Part 1):2010+A1:2013+A2:2015)							
		Environment: CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)							
		Protection: IP67, IK10							
		Must be the same brand with NVR in item #3; Sticker pattern and mounting kits included; Official sealed upon inspection; Warranty: 1 year on parts and services							
3	Network Video Recorder (NVR)	Branded and Brand New	un	1	18,400.00	18,400.00			
		Video/Audio input							
		IP video input: 16-ch							
		Two-way audio input: 1-ch, RCA (2.0 Vp-p, 1kΩ)							
		Network:							
		Incoming bandwidth: 160 Mbps							
		Outgoing bandwidth: 80 Mbps							
		Video/Audio output							
		Recording resolution: 8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF							
		HDMI output resolution: 1-ch, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz							
		VGA output resolution: 1-ch, 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz							
		Audio output: 1-ch, RCA (Linear, 1kΩ)							
		Decoding							
		Decoding format: H.265/H.265+/H.264/H.264+/MPEG4							
		Live view/Playback resolution: 8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF							
		Synchronous playback: 16-ch							
		Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p							
		Network management							
		Network protocols: TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS							
		Hard Disk							
		SATA: 2 SATA interface for 2 HDD							
		Hard Disk Capacity: Up to 6TB for each disk							
		External interface							
		Network interface: 1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface							
		USB interface: 2 × USB 2.0							
		POE Interface							
		Interface: 16, RJ-45 10/100 Mbps self-adaptive Ethernet interface							
		Power: ≤ 150W							
		POE Supported standard: IEEE 802.3 af/at							
		General							
		Power supply: 100 to 240 VAC, 60Hz							
		Power: ≤ 280W							
		Consumption (without hard disk and PoE): ≤15 W							

	Working temperature: -10 °C to +55 °C (14 °F to 131 °F)								
	Working humidity: 10 % to 90 %								
	Chassis: 1U Chassis								
	Dimensions(W × D × H): Approx 385 × 315 × 52 mm (15.2"× 12.4" × 2.0")								
	Weight: Approx. ≤ 3 kg (6.6 lb)								
	Must be the same brand with IP camera in item#2; Surveillance drive mounting screws, sata power cable + sata data cable, USB Optical Mouse, genuine same brand power adapter included; Official sealed upon inspection; Warranty: 1 year on parts and services								
4	Surveillance Hard Drive	Branded and Brand New	pc	2	13,735.00	27,470.00			
	Surveillance Hard Drive type								
	Capacity: 6TB or higher								
	Interface: SATA 6GB/s								
	Features and Performance								
	Drive Bays Supported: 8+								
	Cameras Supported: Up to 64								
	Max. Sustained Transfer Rate OD (MB/s): 195MB/s								
	Cache (MB): 256								
	Reliability/Data Integrity								
	with Tarnish Resistant								
	Load/Unload Cycles: 300,000								
	Nonrecoverable Read Errors per Bits Read, Max: 1 per 10E15								
	Power-On Hours per Year (24×7): 8760								
	Workload Rate Limit (WRL): 180								
	MTBF: 1,000,000hr								
	Power Management								
	Startup Current, Typical (12V, A): 2								
	Average Operating Power (W): 9W								
	Idle Average (W): 7W								
	Standby Mode/Sleep Mode, Typical (W): 0.6/0.6								
	Voltage Tolerance (5V): ±5%								
	Voltage Tolerance (12V): ±10%								
	Environmental/Temperature								
	Operating (ambient, min °C): 5								
	Operating (drive case, max °C): 70								
	Nonoperating (ambient, min °C) -40								
	Officially sealed with anti-static packaging without damage upon inspection; (damaged packaging will not be accepted upon inspection) Warranty: 1 year on parts and services								
Note: CCTV Camera, IP (Item# 2) and Network Video Recorder (NVR) Item# 3 must be of the same brand									
TOTAL ABC						68,320.00			
							TOTAL QUOTED AMOUNT IN WORDS:		

Reviewed and Checked By: /

MAG
 Mark Efrain M. Gironella
 BAC TWG

Please quote at your government price (including VAT) and state that the time within which you can make delivery. It will be appreciated if we can have your quotation in the office as soon as possible on or before the deadline stated herein.

Delvin Magat
 BUYER/ END-USER

TERMS AND CONDITIONS:

1. Price quotation/s shall be valid for a period of at least (30) calendar days from the date of submission.
2. In order to assure that manufacturing defects shall be corrected by supplier, a warranty security shall be required from the contract awardee for a minimum period of **three (3) months**, in the case of EXPENDABLE SUPPLIES, or a **minimum of one (1) year warranty and two (2) to three (3) years extended warranty (if applicable)** in the case of NON-EXPENDABLE SUPPLIES after acceptance by End-user of the delivered supplies.
3. Delivery period within 30 calendar days
4. Award of contract shall be made to the lowest quotation which complies with the technical specifications, and other terms and condition stated herein.
5. UPLB reserves the right to reject any or all offers as may be considered most advantageous to the University.
6. Any interlineations, erasure, or overwriting shall be valid only if they are signed or initiated by you or any of your duly authorized representative/s.

Requirements for Suppliers (GPPB Resolution No. 21-2017)

REQUIREMENTS	Shopping (Section 52)	Negotiated Procurement- Small Value Procurement (Section 53.9)	Negotiated Procurement- Lease of Real Property or Venue (Section 53.10)	Negotiated Procurement- Scientific, Scholarly or Artistic Work, Exclusive Technology and Media Services (Section 53.6)	Negotiated Procurement- Emergency (Section 53.2)
1 Mayor's/Business Permit	/	/	/	/	/
2 PhilGEPS Registration Number	/	/	/	/	/
3 Professional license/ CV (consulting services)		/		/	
4 PCAB License (for infrastructure)		/			
5 Income / Business tax returns (except for government agencies as lessor)		FOR ABC'S ABOVE 500K	/	/	FOR ABC'S ABOVE 50K
6 Omnibus Sworn Statement		FOR ABC'S ABOVE 50K			FOR ABC'S ABOVE 500K
7 NFCC for infrastructure with ABC above Ph500k		/			FOR ABC'S ABOVE 50K

After having carefully read and accepted your General Conditions, I/We quote you on the item at prices noted above.

Name of the Company: _____

Address: _____

Signature over Printed Name of Representative: _____

Position: _____

Tel. No.: _____

Fax No.: _____

Email Address: _____

Date: _____